



# KUL-Bamboo DECKING



The bamboo for our multi-ply bamboo decking grows to maturity within just 5 years and is a sustainable alternative to tropical hardwoods. Besides its high durability, KUL Bamboo decking has the following properties:

- ✓ High dimensional stability - very little moisture expansion and shrinking
- ✓ Uniform material structure - no knotholes, no bleeding etc.
- ✓ Light basic colour - colour can be designed with pigmented oils
- ✓ Not heavier but approx. 38% harder than oak
- ✓ Bamboo decking available in long lengths - up to 4,88 m
- ✓ Installation with small 4-5 mm gaps
- ✓ Easy to install with invisible clip-system
- ✓ Producer holds FSC-certification
- ✓ Natural and original bamboo look
- ✓ Patented production process

Bamboo decking KUL OUT 06, flat top and fine bottom molding  
18,5 mm thickness, side grooves for clips, pre-oiled

profile	length x width m	pcs/ pallet	m <sup>2</sup> aprox./ pallet
KUL OUT 06	3,05 x 0,14	192	82,01
KUL OUT 06	3,66 x 0,14	160	82,01
KUL OUT 06	4,27 x 0,14	136	81,30
KUL OUT 06	4,88 x 0,14	120	82,01
Bamboo Oil	colour nature	unit of 2,5 l	
Clips & Screws	(stainless steel)	21 pcs for 1 m <sup>2</sup>	

Decking and cladding are classified durability class 1 (EN 350 / EN 113)





# KUL-Bamboo CLADDING



Our outdoor bamboo cladding is a functional and prestigious design element. This classic profile is made of multi-ply bamboo, and can be processed like wood. Because of the bamboo's extreme strength, the material should be pre-drilled. All products come pre-oiled, but should receive an initial surface treatment after installation with our proven oil.

Cladding profile KUL SID 02, tongue and groove, pre-oiled, 18 mm thickness.

length x width m	pcs/ pallet	m <sup>2</sup> aprox./ pallet
1,96 x 0,14	217	59,54
3,66 x 0,14	160	82,01



Distributed by:

Lotze & Partner Bambusprodukte GmbH

Desmastr. 3-5

28832 Achim

Tel.: +49 - 4202- 95 50 864 (deutsch)

Tel.: +49 - 4202- 95 51 432 (english)

service@kul-bamboo.com